

DECLARATION OF PERFORMANCE

In compliance with EU Regulation : No 305/2011 of March 2011, Construction Product Regulation (CPR):

1) Unique identification code of the product-type:

CEM I 52,5 R White Portland Cement

2) Type ,batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) : Batch number : see packaging of the product

3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

Architectural and decorative concrete productions, ready-mixed plaster and mortar productions, adhesive and joint filling materials production, park and garden furniture designs, design of works of art, flooring productions, pre-cast component productions, historicals arts restoration works.

4) Name and contact address of supplier: ÇİMSA ÇİMENTO SANAYİ ve TİCARET A.Ş. (MERSİN Plant)

Toroslar Mah. Tekke Cad. 33013 Yenitaşkent / MERSİN

5) Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): Not Relevant

6) System or systems of assessment and verification of constancy of performance of the construction product as set on in Annex V: System 1+

7) In case of the declaration of performance concerning a construction product covered by a harmonised Standard:

EN 197-1:2011 System 1+ :

The notified body (BSI), identification number (0086) performed the initial inspection of the manufacturing plant and of factory production control under System 1+ and issued:

Certificate of conformity of the factory production control (0086-CPD-458580)

8) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued : Not Relevant

9) Declared performance

Essential characteristics	Performance	Harmonised Technical Specification
Compressive strength 2 days	$\geq 30,0$ Mpa	EN 197-1:2011
Compressive strength 28 days	$\geq 52,5$ Mpa	
Initial Setting Time	≥ 45 Min.	
Soundness, Le Chatelier	≤ 10 mm	
Loss On Ignition	$\leq 5,0$ %	
Insoluble Residue	$\leq 5,0$ %	
Sulfur Trioxide	$\leq 4,0$ %	
Chloride	$\leq 0,10$ %	

10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in points 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Hüsnü GÜL

Quality Management Chief

Date : 12 June 2013

Revision Date : 12.06.2013

DoP No : 01